

4x4 4K 60Hz HDMI 2.0 Matrix Switch

Model:CH4450K

Features

- Multi-Input, Multi-Output HDMI Matrix Switch: Connect Up to 4 HDMI Source Devices and Distribute Signals to 4 Displays or Projectors.
- Unleash unparalleled performance with support for 4K @60Hz resolution, YUV4:4:4 color format, and 18Gbps transmission rate.
- Experience Unparalleled High-Definition Audio and Video with HDMI 2.0 and HDCP 2.2 Support.
- Support for 4K Downscaling to 1080P Output: Convert 4K Signals to 1080P for Compatibility with Older Monitors and Projectors.
- Equipped with 3 RS-232 ports and 1 RJ-45 port, this device offers versatile control options to cater to diverse user needs.
- Automatic Setting Memory and Restoration: Device Saves Current Settings During Power Outages and Automatically Loads Them Upon Power Recovery, Ensuring Uninterrupted Operation and a Stable, Reliable User Experience.
- Each Port Supports EDID Management: Effectively Resolves Annoying Issues Such as Incomplete Display, Flickering, and No Display. This Feature Ensures Perfect Compatibility with Various Display Devices, Providing a Stable and Smooth Visual Experience, Allowing You to Enjoy High-Quality Images Without Display Problems.
- Independent Audio Signal Output: Flexibly Output Audio to Different Devices such as Speakers and Headphones, Providing Versatile Audio Solutions.
- Voltage Load Protection: Effectively Reduces the Risk of Equipment Damage, Ensuring Your Safety and Peace of Mind.
- Diverse Control Options: Includes Remote Control, TCP/IP, RS-232, and APP, Offering Flexible and Convenient Operation Choices.
- Effortless HDMI Management: Buttons with LED Status Display for Easy Input/Output Monitoring.
- 1U Rack Installation with Premium LED Display: Advanced Front Panel Design for Optimal Performance and Control.

Package Contents

- 1 X CH4450K
- 1 X 12V/ 2A adapter
- 1 X Remote control (Battery not provided)
- 1 X User manual

Diagram



Specification

| | |
|-----------------------------------|---|
| Model Name | CH4450K |
| Input | 4 x HDMI |
| Output | 4 x HDMI, 1 x 3.5mm, 1 x SPDIF |
| Video resolution | 4K @60Hz, YUV4:4:4 backward compatible. (Max) |
| Color depth | 48/ 36/ 30/ 24-bit |
| Protocol standard | Support HDMI2.0, HDCP2.2 and DVI 1.0 |
| Control method | Button, Remote control, 3xRS-232, 1xTCP/IP, APP |
| The length of the connecting wire | It can be connected to a 28AWG HDMI2.0 cable with a maximum length of 5 meters, with the combined input and output length not exceeding 10 meters. For distances beyond this, using an extender is recommended. |
| Power supply | DC 12V/ 2A |
| Dimensions | 482 x 288 x 44mm (LxWxH) |
| Weight | 3.4Kg |